

REDUNDANT

MRW-5600G // SLEEVED // 600WATT



Product: PSU

Form factor: PSII

Color: silver

If you are looking for "green-power" and high-performance 24-7, then the MRW-5600G will be the choice.

Certificates:



Technical data

Specification: ATX 12V 2.3

Efficiency: >90%

Dimensions (DxWxH): 185mm x 150 mm x 87 mm

PCF: Active PFC (0,9)

Fan: 40mm fan (2x 40mm per module)

Connectors

24 PIN	8PIN EPS	System LED	SATA	Molex	Floppy	TTL Signal Kabel	Buzzer	
1	1	0	6	9	1	1	1	
8PIN EPS (4+4)	6PIN PCIe	8 PIN PCIe (6+2)						
1	0	0						

DC Output / AC Input

AC INPUT: 100V / 9A 240V / 4A FREQUENCY: 47 - 63 HZ MAX. LOAD: 600W	DC OUTPUT								
	+5V	+3,3V	+12V1	+12V2	+12V3	-5V	P.F.	-12V	+5VSB
	25A	25A	49A	N/A	N/A	N/A	>0,9	0,8A	3,5A
	170W		N/A						

Security:

Met.al frame, 2x 600W modules, TTL-Signal, Buzzer- LED Alarm, hot-swap, hot-plug features, full range Input 100V~240V, Meet FCC, CISPR EMI regulation, Balanced load sharing design, UVP; OVP; SCP; OPP; OCP; OTP; AFC

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.