



Hewlett Packard
Enterprise

HPE G2 METERED/SWITCHED 3PH 11KVA/60309 5-WIRE 16A/230V OUT (18) C13 (6) C19/VERTICAL INTL PDU (P9S20A)

Power Distribution Units



WHAT'S NEW

- HPE G2 Metered and Switched Power Distribution Units (PDU) are rated for operating temperatures of up to 60°C (or 140°F).

OVERVIEW

Looking for a flexible, accurate power distribution solution that allows metering and switching at the outlet level and supports both local and remote power management?

The HPE G2 Metered and Switched Power Distribution Unit

- Color-coded receptacles on single and three phase models to easily distinguish between the different load segments/phases.
- A hot swappable Network Management Card (NMC) allowing for power to remain distributed with the removal of the management card thus creating zero down time.
- Enhanced environmental sensor options on the G2 Metered and Switched PDUs for monitoring temperature, humidity, intrusion, and water leakage within the rack.
- Choose the optional Locking Power Cord for secure cable retention to both the PDU and target device.

(PDU) provides both local and remote power management with outlet-level power metering and switching. An LCD screen provides local monitoring and alert indications, while remote access and configuration are available through secure Web, SNMP, CLI, or Telnet interfaces. Remote outlet monitoring offers $\pm 1\%$ billing grade accuracy while remote switching capabilities support power on/off functionality to remotely reboot equipment or restrict outlet usage. The G2 Metered and Switched PDU features a low-profile, single-piece design with multiple mounting options and ease of access to rear devices for maintenance. It is compatible with all Advanced and Enterprise Series Racks, as well as with many non-HPE racks using standard button and keyhole mounting.

FEATURES

Local And Remote Power Distribution Management With Billing Grade Accuracy

HPE G2 Metered and Switched Power Distribution Units (PDU) include local and remote access to on/off outlet switching and metering, remotely reboot equipment, or restrict outlet usage.

Remotely access and configure each PDU through secure Web, SNMP, CLI, or Telnet Interfaces with the ability to daisy-chain up to four units to share the same network connection and IP address.

Local access, monitoring, and alert notifications available through new OLED display technology.

Meets IEC 62053-21, Class 1 standards for $\pm 1\%$ or better accuracy in power metering.

Operational capability to 60°C in the rear of the rack ensures continuity of power should rack temperatures spike.

Flexible, Simple Installation and Maintenance

HPE G2 Metered and Switched Power Distribution Units (PDU) feature a low-profile, single-piece design supporting multiple mounting options and ease of access to rear devices for maintenance.

Install PDU units side by side on both sides of the rack with the outlets facing in towards the center of the rack for high density configurations.

Support for integrated power cord retention on all IEC receptacles that work with standard power cords.

Add an optional environmental sensor which can measure air temperature and humidity in the front or rear of the rack, sending alerts over the network based on user-defined thresholds.



Safely and securely manage your IT Equipment

HPE G2 Metered and Switched Power Distribution Units (PDU) offer remote access through industry-first PDU support for 1Gb Ethernet allows power on/off capabilities to remotely reboot equipment or restrict outlet usage.

Supports both Local and LDAP security with multiple access levels to provide enhanced security.

Protects against accidental circuit overload while providing the tools to optimize power management in the rack.

Compatible With a Wide Range of HPE and Non-HPE Rack Solutions

HPE G2 Metered and Switched Power Distribution Units (PDU) are designed to provide complete compatibility with Advanced and Enterprise Series racks.

The PDU is also compatible with a wide range of non-HPE racks using standard button and keyhole mounting.

Designed for vertical/OU rack configurations offering both half and full-height form factors.

Technical specifications

HPE G2 Metered/Switched 3Ph 11kVA/60309 5-wire 16A/230V Out (18) C13 (6) C19/Vertical INTL PDU

Product Number (SKU)	P9S20A
Mounting options	OU/Vertical
Outlet type	C-13 and C-19
Power capacity	Greater than 10kVA
Power distribution	Three Phase
Number of included PDU sticks	0
Product Dimensions (metric)	20.80 x 197.99 x 11.61 cm
Weight	7.80 kg
Warranty	HPE G2 Metered and Switched Power Distribution Units are supported with a limited 3-year warranty which automatically assumes the HPE service coverage level of any covered HPE ProLiant server in the same rack.



Most, if not all IT organizations are on a digital transformation journey — each at a different stage. With over 11,000 IT projects conducted and 1.4 million customer interactions each year, [HPE Pointnext Services](#)' 15,000+ experts and its vast ecosystem of solution partners and channel partners are uniquely able to help you at every stage of your digital transformation. We bring together technology and expertise to help you drive your business forward and prepare for whatever is next.

Advisory and Professional Services help you accelerate your digital transformation. [Operational Services](#) help you remove complexity and respond rapidly to business demands.

Operational Services from HPE Pointnext Services

[HPE Pointnext Tech Care](#) provides fast access to product-specific experts, an AI-driven digital experience, and general technical guidance to help enable constant innovation. We have reimagined IT support from the ground up to deliver faster answers and greater value. By continuously searching for better ways to do things—as opposed to just fixing things that break—HPE Pointnext Tech Care helps you focus on achieving your business goals.

- **[HPE Datacenter Care](#)** helps modernize and simplify IT operations. Partner with an assigned account team, access technical expertise, an enhanced call experience gives you priority access, choose hardware and software support, implement proactive monitoring to help stay ahead of issues, and access HPE IT best practices and IP.
- **[HPE Proactive Care](#)** offers an enhanced call experience and helps reduce problems with personalized proactive reports and advice. This also includes collaborative software support for Independent Software Vendors (ISVs), (Red Hat, VMWare, Microsoft, etc.). [Read more](#)
- **[HPE Foundation Care](#)** helps when there is a problem and has a choice of response levels. Collaborative software support is included and provides troubleshooting help for ISVs running on your server. [Read more](#).

Other related services

[Defective Media Retention](#) is optional and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

[HPE Service Credits](#) offers a menu of technical services, access additional resources, and specialist skills.

[HPE Education Services](#) delivers a comprehensive range of services to support your people as they expand their skills required for a digital transformation.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and support options.



For additional technical information, available models and options, please reference [the QuickSpecs](#)

HPE GREENLAKE

HPE Greenlake is HPE's market-leading IT as-a-Service offering that brings the cloud experience to apps and data everywhere – data centers, multi-clouds, and edges – with one unified operating model. HPE GreenLake delivers public cloud services and infrastructure for workloads on premises, fully managed in a pay per use model.

If you are looking for more services, like **IT financing solutions**, please [explore them here](#).

**Make the right purchase decision.
Contact our presales specialists.**

[Find a partner](#)



Chat now (sales)



Call now



Buy now



Share now



Get updates


**Hewlett Packard
Enterprise**

© Copyright 2021 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product
[PSN1009830219CZEN](#), September, 2021.