

| RLK8-520B2D2-NVR-Kit-NVR-Specifications |                               |                                                                                                                                       |
|-----------------------------------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
|                                         | Model                         | RLN8-410                                                                                                                              |
| Video/Audio Input                       | IP Video Input                | PoE IP Camera x 8                                                                                                                     |
|                                         | Audio Input                   | Cameras with Built-in Mic                                                                                                             |
| Video/Audio Output                      | HDMI Output                   | 3840x2160, 1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768                                                               |
|                                         | VGA Output                    | 1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768                                                                          |
|                                         | Audio output                  | 1CH RCA                                                                                                                               |
| Decoding                                | Live View/Playback Resolution | 3840x2160, 2560x1920, 2560x1440, 2048x1536, 2304x1296, 1080p, 720p                                                                    |
|                                         | Frame Rate                    | PAL: 4CH@25fps; NTSC: 4CH@30fps                                                                                                       |
|                                         | Synchronous Playback          | 1CH@8MP; 4CH@4MP                                                                                                                      |
| HDD                                     | SATA Devices                  | 1 x 2TB SATA HDD                                                                                                                      |
|                                         | Maximum Capacity              | 8TB (Maximum 4TB HDD/Port)                                                                                                            |
|                                         | External HDD                  | 1 x eSATA                                                                                                                             |
| External Interface                      | USB Interface                 | 2 x USB 2.0                                                                                                                           |
|                                         | Network Interface             | RJ45,10M/100M Ethernet, 8 Network Ports for IP camera, 1 Giga Network Port for LAN/WAN                                                |
| PoE                                     | Interface                     | 8 Independent 100 Mbps PoE Network Interfaces                                                                                         |
|                                         | Max. Power Consumption        | 25W                                                                                                                                   |
|                                         | Supported Standard            | IEEE 802.3at                                                                                                                          |
| Network                                 | Network Protocol              | HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP                                                          |
|                                         | Browser Supported             | IE, Firefox, Chrome                                                                                                                   |
|                                         | OS Supported                  | PC: Windows, Mac OS; SmartPhone: iOS, Android                                                                                         |
|                                         | Max. User Access              | 20 Users                                                                                                                              |
| General                                 | Power Supply                  | DC 48V/2A                                                                                                                             |
|                                         | Power Consumption             | <10W (Without HDD&PoE)                                                                                                                |
|                                         | Working Environment           | Temperature: -10℃~+45℃ (14°F~113°F); Humidity: 10%~90%                                                                                |
|                                         | Dimensions (mm)               | 260(W) x 41(H) x 230(D)                                                                                                               |
|                                         | Weight (w/o HDD)              | 1.2 kg                                                                                                                                |
| Warranty                                | Limited Warranty              | 2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> |