


Eaton Gigabit Network Card



Enhanced capabilities, unmatched security

Eaton's Gigabit Network Card (Network-M3) UPS connectivity device expertly blends comprehensive power management with market-leading cybersecurity. The Gigabit Network Card was the first to market with cybersecurity certifications obtained from independent authorities (UL 2900-1 and IEC 62443-4-2), and the new M3 version builds on this innovation with a zero-trust architecture that makes it even more effective at protecting mission-critical systems in medium-sized and enterprise IT networks. The Gigabit Network Card is compatible with multiple Eaton power management software solutions, allowing extensive automation and remote management and control that shortens response times to power issues. The Gigabit Network Card gives IT managers actionable intelligence for proactively addressing power problems before they turn into downtime, and for maximizing the efficiency of their power operations.

- **Zero-trust architecture** minimizes cybersecurity vulnerabilities through hardware *root of trust*, enabling secure boot and complete chain of trust
- **Zero-touch provisioning** automatically configures network cards faster, saving time exponentially in large-scale deployments
- **Brightlayer Data Centers suite** monitors and manages fleets of Gigabit Network Cards, enabling automated actions during power events, including graceful shutdown and reallocation of virtual machines to protect data and preserve business continuity
- **User-configurable firewall** reduces an organization's attackable surface area and helps meet specific network/security compliance requirements
- **REST API** allows organizations to easily integrate the network card with native systems and automate M2M interactions

Optional monitoring probe

Connect multiple environmental sensors to your Gigabit Network Card with Eaton's Environmental Monitoring Probe (EMP) Gen 2 (EMPDT1H1C2). This probe provides data on the temperature and humidity in your IT installation, as well as dry-contact monitoring. It can be daisy-chained (up to 3 per host), allowing multiple sensor connections to a single host.w




Eaton's Gigabit Network Card is the only device of its kind to obtain UL 2900-1 and IEC 62443-4-2 cybersecurity certifications.

Technical specifications¹

Function	Web/SNMP communications
Hardware compatibility (global list)	UPS²: 5P, 5PX, 5PX G2, 5SC Rack, 9PX, 9SX, 9130, 9E, 93PS (fw 2.50->), 91PS, 91PS Monoblock, 93E 15-80 EMEA (fw 8.00.01->), 93E G2 EMEA (fw 4.0.20->) PDU: EATS16N
Network compatibility	IPv4/v6, TLSv1.2, HTTP(S)v1.1, NTP, SMTP(S), BOOTP/DHCP, SSH, SysLog(S), LDAP, AD, RADIUS
Catalog number	Network-M3
Protocol support	HTTPS1.1, MQTTS, TLS1.2, SNMPv1, SNMPv2c, SNMPv3, NTP, SMTPS, BOOTP/DHCP, CLI, SSH, ARP and Syslog
UPS slot type	Mini-slot
Common connectors	Ethernet 10/100/1000BaseT, USB for accessories (ex: Environmental Monitoring Probe), USB configuration port
Temperature and humidity monitoring	Yes. Requires Eaton Environmental Monitoring Gen 2
Supported software	Brightlayer Data Centers software suite: Data Center Performance Management (DCPM), Distributed IT Performance Management (DITPM), Visual Power Manager (VPM), Intelligent Power Manager (IPM) and Visual Capacity Optimization Manager (VCOM); for monitoring service software: PredictPulse (Americas) or Cyber Secured Monitoring (CSM, for EMEA)
Supported MIB	MIB II – Standard IETF UPS MIB (RFC 1628) – Eaton xUPS MIB
Supported browsers	Chrome, Edge
Local language support	English, French, German, Italian, Spanish, Chinese Simplified, Chinese Traditional, Japanese
Operating temperature	0 to 40° C
Operating humidity	90% RH max. without condensation
Power input	5 V – 12 V
Current consumption	500/1000mA max. depending on UPS
Dimensions (H x W x D)	41 x 66 x 135 mm
Weight	65 g
Regulatory	Same as UPS

1. Due to continuous product improvements, program specifications are subject to change without notice.
2. Select Eaton UPS models include the Network M-3 as a bundle purchase.



Eaton Gigabit Network Card installed in a UPS

For more information, please visit:
Eaton.com/au/Network-M3

© 2024 Eaton
All Rights Reserved

May 2024

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

